

mpower[®] Traffic Controller



Versatile traffic controller with a durable, silicone lens



FEATURES



- Ability to mount in any direction (front, rear, left and right) with separate controls for each facing
- Excellent for blockers, vehicles diverting traffic, angling vehicles and so much more
- Intended for interior or exterior use
- Available in lengths of four, five, six, eight (split or full) or ten modules
- Wire harness lengths available in 3, 15 or 25 feet
- Designed with six inch high powered, wide angle modules

SPECIFICATIONS

Input Voltage Range	9-32 Vdc		
Amperage Draw	1.14 amps per module (flashing) 1.9 amps per module (peak)		
Wattage	14.6 watts per module (flashing) 24.3 watts per module (peak)		
Operating Temperature	-40°C to +65°C / -40°F to +150°F		
LED Color Capabilities	Single, dual, tricolor		
LED Color Options			
Lens Color Options	Clear, Stealth		
LED Count	Single - 6 LEDs, Dual - 12 LEDs, Tricolor - 18 LEDs		
Dimensions	Lengths: 4 module: 26" (66 cm) 5 module: 32.5" (82.5 cm) 6 module: 38.75" (98 cm)	8 module: 52" (133 cm) 8 module split: (2) 26" (66 cm) 10 module: 64.25" (163 cm)	Height: 1.6" (3.9 cm) Depth: 2.4" (6.2 cm)
Mount Types	Universal mounting for front, rear, left or right fitment, various bracket sizes available		
Housing Material	Aluminum housing		
Certifications*	SAE J595, SAE J845, CA Title 13, Article 22 compliant		
IP Rating	IP67		
Warranty	Five year		

*Valid when using compliant patterns and configurations



Scan to order
or learn more

Visit soundoffsignal.com to configure to your exact needs.

CONTACT

Toll free 800-338-7337
Direct 616-896-7100
soundoffsignal.com

3900 Central Pkwy
Hudsonville, MI 49426
customerservice@soundoffsignal.com

V0525